109 cm (43") Full HD LCD/TFT Monitor

GD-ML-BP4330HD







Type: Full HD - LCD/TFT - Monitor Item Code: GD-ML-BP4330HD EAN CODE: 4260573063093

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Features

- Designed for professional 24/7 usage
- Including IR Remote Control

- Displays a full, flat 43" (109cm) diagonal image
- LED Backpanel illumination

109 cm (43") Full HD LCD/TFT Monitor

GD-ML-BP4330HD



Specifications GD-ML-BP4330HD

Display

LCD Panel size: 109 cm (43") Diagonal AM-TFT LED Backlight

Pixels - Total: 1920 (H) x 1080 (V)

Pixel Pitch: 0.248 mm (H) x 0.248 mm (V)

Aspect Ratio: 16:9

Viewing Angle: 178° (H) ~ 178° (V)

Video

Video Inputs: 2x HDMI, 1x VGA, 1x AV

Video Standard:PAL, NTSCBrightness:500 cd, m²Contrast Ratio:1000:1Number of Colours:16.7 million

Response Time: 5 ms

General

Speakers: 2 x 5 W

OSD (On Screen Display): Yes, multi language

Accessories included: Stand, power cable, HDMI cable and remote control

I/O Interface

Audio Inputs: 1-ch, RCA (2.0 Vp-p, $1k\Omega$)

Approvals

Regulation: CE, EAC, FCC, RoHS Compliant

MTBF at 25° C: > 50,000 hours

Environmental

Operating Temperature: 0 °C ~ +40 °C

Humidity: Less than 90%, non condensing

Electrical

Supply Voltage: 100 ~ 240 VAC, 50Hz / 60Hz

Power Consumption: Max. 95 W

Mechanical

Material: Robust Plastic

Vesa Mount: 200 x 200 mm

Dimensions: 969 x 565 x 87 mm

Weight: 7900 g (17.42 lb)