

140 cm (55") 4K UHD LCD/TFT Monitor

GD-ML-BP5540UHD

GRUNDIG



Type: 4K - LCD/TFT - Monitor

Item Code: GD-ML-BP5540UHD

EAN CODE: 4260573063758

PROFESSIONAL

The PROFESSIONAL product line comprehensively covers modern video systems and offers versatile solutions for various areas of application.

Highlights

Continuous operation



This Grundig Security device is capable of operating 24/7 continuously on any day.

Features

- Designed for professional 24/7 usage
- LED Backpanel illumination
- Ultra High Definition (UHD) TFT-LCD monitor

Specifications GD-ML-BP5540UHD

Display

LCD Panel size:	140 cm (55") Diagonal AM-TFT LED Backlight
Pixels - Total:	3840 (H) x 2160 (V)
Pixel Pitch:	0.315 mm (H) x 0.315 mm (V)
Aspect Ratio:	16 : 9
Viewing Angle:	178° (H) ~ 178° (V)

Video

Video Inputs:	1x Display Port, 3x HDMI
Video Standard:	PAL, NTSC
Brightness:	350 cd, m ²
Contrast Ratio:	4000:1
Number of Colours:	1073 G
Response Time:	5 ms

General

OSD (On Screen Display):	Yes, multi language
Accessories included:	Power Adapter and HDMI cable, remote control

Approvals

Regulation:	CE, EAC, FCC, RoHS Compliant
MTBF at 25° C:	> 50,000 hours

Environmental

Operating Temperature:	0 °C ~ +45 °C
Humidity:	Less than 90%, non condensing

Electrical

Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. 130 W

Mechanical

Material:	Metal
Vesa Mount:	400 x 400 mm
Dimensions:	1233 x 705 x 46 mm (48.5 x 27.8 x 1.8 inch)
Weight:	16000 g (35.3lb)