



Type: Switch - Transmission - Hardware

Item Code: GD-HW-ACSW16R

EAN CODE: 4260573064793



### ESSENTIAL

Our ESSENTIAL product line is designed to deliver high-quality performance, with basic features and impressive functions, making it perfect for smaller applications.

## GD-HW-ACSW16R Highlights

A high-quality network switch is equipped with a comprehensive set of features. It includes 16 × 10/100 Mbps PoE ports, and 2 × 10/100/1000 Mbps RJ45 ports, offering flexibility and versatility in network connectivity. The Hi-PoE port adheres to the IEEE 802.3at/af/bt standard, providing a maximum power of 60 W for devices connected to this port.

The PoE ports operate according to the IEEE 802.3at/af standard, delivering power efficiently. The switch supports various network standards, such as IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z, ensuring compatibility and seamless integration with other network devices.

To ensure reliability and protection, the switch provides 6 KV surge protection for the PoE ports. Additionally, the switch supports extended mode for AF/AT cameras, offering a maximum reach of up to 250 m. Hi-PoE cameras can reach up to 150 m, providing flexibility in camera placement and installation.

The switch incorporates advanced PoE power management capabilities, optimizing power distribution and ensuring efficient operation. With a dual uplink network design, the switch offers redundancy and enhanced network connectivity.

With wire-speed forwarding and a non-blocking design, the switch ensures fast and uninterrupted data transmission. It utilizes a store-and-forward switching method, enhancing data integrity and reducing packet loss.

The switch's solid high-strength metal shell provides durability and protection, ideal for industrial or harsh environments. Furthermore, its fan-free design ensures reliable and noiseless operation.

Overall, this network switch delivers advanced features and reliable performance, making it an excellent choice for various networking applications

## Features

- Layer 2 PoE network switch, providing 16 × Gigabit PoE ports and 2 × Gigabit SFP fiber optical ports. On top of high-performance access, the switch provides advanced PoE power technology to guarantee the stable network upload of the adaptive data.
- PoE power management
- 6 KV surge protection for PoE ports
- Gigabit network access

## Specifications GD-HW-ACSW16R

### General

PoE Specification:	802.3af/at (PSE)
Switching Method:	Store and Forward
Accessories included:	Power cable, 19 inch rack mount kit

### Network

MAC Address Table:	8K
Internal Cache:	4.1 Mbits
Packet Forwarding Rate:	26.784 Mpps
Switching Capacity:	36 Gbps

### I/O Interface

ISO Standard:	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
PoE Budget:	230 W
PoE Power Pin:	1/2(+), 3/6(-)
Ports:	16 x 10/100/1000 Base-T PoE RJ45(Auto-MDI/MDI-X) 2 Gigabit SFP fiber optical ports

### Approvals

Certifications:	CE, FCC, RoHS
-----------------	---------------

### Environmental

Operating Temperature:	-10°C ~ +55°C (+14°F ~ + 131°F)
Operating Humidity:	5% ~ 95%, non-condensing
Storage Temperature:	-40°C ~ +85°C

### Electrical

Surge Protection:	TVS 6000V Lightning Protection, Surge Protection and Voltage Transient Protection
Max power Output per Port:	54V DC, 30 watts max
Supply Voltage:	100 ~ 240 VAC, 50Hz / 60Hz
Power Consumption:	Max. power consumption 250W Power consumption in idle 25W

### Mechanical

Material:	Metal
Dimensions:	440 x 221 x 44 mm (17.3 x 8.7 x 1.7 inch)
Weight:	2700 g (5.95lb)

### Packaging

Package Dimensions:	170 x 170 x 150 mm (6.7 x 6.7 x 5.9 inch)
Package Weight:	3600 g (7.9 lbs)
Packaging Unit:	8
Bulk Package Dimensions:	545 x 391 x 337 mm (21.5 x 15.4 x 13.3 inch)
Bulk Package Weight:	13800 g (30.4 lbs)

## Dimensions

