

# Corrugated plastic conduits

FFKu®-EL-F

22212



- Pliable corrugated plastic conduit
- Light compressive strength
- Light impact strength
- Temperature range from -5 °C to +60 °C
- Material: PVC-U
- Corrosion-resistant

EN 61386-22  
Minimum compressive strength:  
320 N/5 cm



Cat. no.	Type	Outside Ø* [mm]	Inside Ø [mm]	Coil content [m]	Coil weight [kg]	Pallet content [m]	Bend radius ≥ [mm]	Colour
<b>25010016</b>	16	16.0	11.0	100	3.3	2400	60	beige
<b>25010020</b>	20	20.0	14.5	100	4.7	2000	80	
<b>25010025</b>	25	25.0	18.8	50	2.7	1000	100	
<b>25010032</b>	32	32.0	24.5	50	4.4	800	130	
<b>25010040</b>	40	40.0	31.7	25	2.9	400	170	
<b>25010050</b>	50	50.0	40.3	25	4.2	400	220	
<b>25010063</b>	63	63.0	50.7	25	5.3	150	250	
<b>25005016</b>	16	16.0	11.0	50	1.6	2100	60	light grey
<b>25005020</b>	20	20.0	14.5	50	2.3	1500	80	
<b>25005025</b>	25	25.0	18.8	50	2.7	1200	100	
<b>25005032</b>	32	32.0	24.5	25	2.2	600	130	
<b>25005040</b>	40	40.0	31.7	25	2.9	400	170	
<b>25005050</b>	50	50.0	40.3	25	4.2	400	220	
<b>25005063</b>	63	63.0	50.7	25	5.3	150	250	

\* Production-related dimensional tolerances acc. to EN 60423.

For suitable accessories, please refer to the Corrugated plastic conduit accessories section (pages 19–22).