

Toote infoleht

Tehnilised andmed



Fire detection panel, Esmi Fire detection panels, FXS 3NET, for Estonia

FFS00703814EE

Main

Range of product	Esmi fire detection panels
Product or component type	User interface
Colour	Cover light blue/grey NCS S 4020-R80B) Collar dark blue/grey NCS S 5020-R80B) Frame dark grey NCS S 7502-B)
Maximum allowed current consumption	0.5 A 24 V DC standby 1.0 A 24 V DC alarm

Complementary

Operating voltage range	19...30 V DC
Device composition	cover plastic frame sheet steel/plastic back frame sheet steel
Height	328,0 mm
Width	417,0 mm
Depth	79,0 mm
Product weight	4,4 kg without batteries
Addressable loop controller	ALC/SLC
Number of loops	2 addressable
Number of addresses	0...159 addressable detectors and call points for SLC 0...159 other modules for SLC 0...126 addressable devices for ALC
Optional circuit board slots	1 optional circuit board
Product compatibility	Fireman's panel FMPX/FMP2 Protocol repeater REPX/REPX-OB Delay alarm panel DAPX/DAP2 Logical controller MCOX/MCOX-OB LED panels for fire zones ZLPX

Environment

Standards	EN 54-2
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	5...40 °C
Ambient air temperature for storage	0...50 °C

IP degree of protection	IP30
-------------------------	------

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	4640,0 g
Pakk 1 kõrgus	10,0 cm
Pakk 1 laius	34,0 cm
Pakk 1 pikkus	44,0 cm

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Contractual warranty

Garantii	24 months
----------	-----------
