

Product data sheet

Specifications



Open-area sounder beacon, configurable

FFS06728118

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Audible visual alarm device

Complementary

Colour tint	Base: red Lens: red
[Ue] rated operational voltage	17...28 V DC polarity sensitive
Current consumption	450 μ A at 24 V DC standby 8.2 mA at 24 V DC alarm 1.2 mA at 24 V DC power-up surge < 1 s
Signalling type	15 evacuation tones 15 secondary or alert tones
Acoustic level	100 dBA at 90°
Type of setting	Volume: 7 levels settings
Local signalling	LED red flashing at 1 Hz: alarm
Diameter	98 mm
Height	104 mm
Net weight	265 g

Environment

Standards	EN 54-3 EN 54-17
Product certifications	CPR LPCB
IP degree of protection	IP65
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5 cm

Package 1 width	12.5 cm
Package 1 Length	12.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information