



## Main

Range of product	Esmi addressable components for SLC range
Product or component type	Thermal detector
Detection type	Heat

## Complementary

[Ue] rated operational voltage	15...32 V DC
Current consumption	160 µA at 24 V DC standby 300 µA at 24 V DC standby LED on 3.5 mA at 24 V DC alarm LED on 10.8 mA at 24 V DC remote LED
Material	PC/ABS
Output type	Remote LED optional
Alarm threshold	78 °C
Colour	White
Cable cross section	0...2.5 Mm <sup>2</sup>
Diameter	With mounting base: 102 mm
Height	61 Mm (with mounting base)
Product weight	88 G with mounting base

## Environment

Standards	Class BS EN 54-5
Product certifications	CPD
Relative humidity	10...93 % non-condensing
Ambient air temperature for operation	-30...80 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	98.0 G
Package 1 Height	6.0 Cm
Package 1 width	10.0 Cm
Package 1 Length	10.0 Cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Product Life Status : **Commercialised**