

Product data sheet

Specifications



Sounder, ESI-40, weatherproof, 100 dB, red

FFS06728040

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Audible alarm device
Colour tint	Red

Complementary

[Ue] rated operational voltage	18...28 V DC polarity sensitive
Current consumption	330 µA at 24 V DC standby 5 mA at 24 V DC alarm 1.2 mA at 24 V DC power-up surge < 1 s
Signalling type	3 tones alarm
Acoustic level	89...103 dBA
Height	110 mm
Width	110 mm
Depth	113 mm
Net weight	294 g

Environment

Standards	EN 54-3
Product certifications	LPCB CPD
IP degree of protection	IP66
Ambient air temperature for operation	-20...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5 cm
Package 1 width	12.5 cm
Package 1 Length	12.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
