

Product data sheet

Specifications



Base sounder beacon, ESI-60, addressable

FFS06728060

Main

Range of product	Esmi addressable components for ALC range
Product or component type	Mounting base

Complementary

Product destination	Audible visual alarm
Colour tint	Body: white
Device composition	body in PC (polycarbonate) contacts in stainless steel
[Ue] rated operational voltage	17...28 V DC polarity sensitive
Current consumption	300 µA at 24 V DC standby 8 mA at 24 V DC alarm 1.2 mA at 24 V DC power-up surge < 1 s
Acoustic level	91 dBA at 90°
Local signalling	LED red flashing at 1 Hz: alarm
Diameter	115 mm
Height	38 mm
Net weight	160 g

Environment

Standards	EN 54-3 EN 54-17
Product certifications	LPCB CPR
IP degree of protection	IP21C
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-20...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5 cm

Package 1 width	12.5 cm
Package 1 Length	12.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
