

Toote infoleht

Tehnilised andmed



Manual call point, MCP5A-RP02FF-01, resettable unit, with isolator

FFS06423742EN

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Manual call point
Colour tint	Red RAL 3001)

Complementary

Material	PC/ABS
Control type	Resettable
[Ue] rated operational voltage	30 V DC maximum
Current consumption	500 µA 24 V DC standby 7.6 mA 24 V DC alarm
Cable cross section	0,5...2,5 mm ² cable
Height	93 mm
Width	89 mm
Depth	27,5 mm
Product weight	130 g

Environment

IP degree of protection	IP24D
Ambient air temperature for operation	-10...55 °C
Standards	EN 54-11
Product certifications	CPD LPCB
Relative humidity	0...96 % non-condensing

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	120,0 g
Pakk 1 kõrgus	3,0 cm
Pakk 1 laius	10,0 cm

Pakk 1 pikkus	9,0 cm
---------------	--------

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
--------------	-------------------------------------

ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
--------------------	--

Elavhõbedavaba	Jah
----------------	-----

RoHS eranditeave	Jah
------------------	---------------------

Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.
-------------------------	--
