

# Toote infoleht

Tehnilised andmed



## Dual input - single output module, EM221EA, with isolator

FFS06717022

### Main

Range of product	Esmi addressable components for SLC range
Product or component type	Input/output module

### Complementary

[Ue] rated operational voltage	15...32 V DC
Current consumption	140 $\mu$ A 24 V DC standby 5.5 mA maximum
Load current	2 A 30 V DC resistive relay output
Local signalling	LED blinking green polling LED red alarm LED green relay active
Provided equipment	Isolator
Cable cross section	0...2,5 mm <sup>2</sup>
Number of inputs	2 input circuit
Number of outputs	1 relay output
Length	97 mm
Height	22 mm
Width	93 mm
Net weight	118 g

### Environment

Standards	EN 54-17 EN 54-18
Product certifications	CPR
IP degree of protection	IP30
Relative humidity	5...95 % non-condensing
Ambient air temperature for operation	-20...60 °C

### Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1

<b>Pakk 1 kaal</b>	118,0 g
<b>Pakk 1 kõrgus</b>	2,2 cm
<b>Pakk 1 laius</b>	9,7 cm
<b>Pakk 1 pikkus</b>	9,2 cm