

# Product data sheet

Specifications



## Base sounder, ESI-30, integrated, no isolator

FFS06728030

### Main

Range of product	Esmi addressable components for ALC range
Product or component type	Mounting base

### Complementary

Product destination	Audible alarm
Colour tint	Body: white
Device composition	body in PC (polycarbonate) contacts in stainless steel
[Ue] rated operational voltage	17...28 V DC polarity sensitive
Current consumption	1.2 mA at 24 V DC standby 5 mA at 24 V DC alarm 1.2 mA at 24 V DC power-up surge < 1 s
Signalling type	2 tones alarm
Acoustic level	83 dBA EN 54 91 dBA at 90°
Diameter	115 mm
Height	38 mm
Net weight	140 g

### Environment

Standards	EN 54-3
Product certifications	LPCB CPR
IP degree of protection	IP21D
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-20...60 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	5 cm

---

<b>Package 1 width</b>	12.5 cm
<b>Package 1 Length</b>	12.5 cm

---

## Offer Sustainability

---

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information

---