

Toote infoleht

Tehnilised andmed



Detector base sounder, BSO-PP-I33, with isolator

FFS06711721

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Mounting base

Complementary

Product destination	Audible alarm
Colour tint	Body pure white Base pure white
[Ue] rated operational voltage	15...28 V DC
Current consumption	225 μ A standby alarm
Signalling type	32 tones alarm
Acoustic level	92...98 dBA 1 m
Type of setting	Volume low Volume medium Volume high
Cable cross section	1,5...2,5 mm ²
Diameter	121 mm
Height	64 mm low profile) 119 mm deep base) 119 mm waterproof base)
Net weight	202 g

Environment

Standards	EN 54-3 EN 54-17
Product certifications	LPCB CPD
IP degree of protection	IP24 with low profile base IP44 with deep base IP65 with waterproof base
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-25...70 °C

Pakke osad

Osa tüüp pakil 1	PCE
------------------	-----

Osade arv pakis 1	1
Pakk 1 kaal	230,0 g
Pakk 1 kõrgus	6,0 cm
Pakk 1 laius	12,5 cm
Pakk 1 pikkus	12,5 cm

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.