

Toote infoleht

Tehnilised andmed



Sounder, WSO-PR-N33, without isolator, wall mounted

FFS06711738

Main

Range of product	Esmi addressable components for SLC range
Product or component type	Audible alarm device
Colour tint	Body red Base pure white

Complementary

[Ue] rated operational voltage	15...32 V DC
Current consumption	120 µA 24 V DC standby 11.4 mA 24 V DC alarm
Signalling type	32 tones alarm
Acoustic level	94...100 dBA at 1m
Type of setting	Volume low Volume medium Volume high
Cable cross section	1,5...2,5 mm ²
Device mounting	Base mounting low profile Base mounting deep base Base mounting waterproof base
Diameter	121 mm
Height	64 mm (low profile) 119 mm (deep base) 119 mm (waterproof base)
Net weight	238 g

Environment

Standards	EN 54-3
Product certifications	LPCB CPD
IP degree of protection	IP24 with low profile base IP44 with deep base IP65 with waterproof base
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	-25...70 °C

Pakke osad

Osa tüüp pakil 1	PCE
Osade arv pakis 1	1
Pakk 1 kaal	268,0 g
Pakk 1 kõrgus	6,5 cm
Pakk 1 laius	12,5 cm
Pakk 1 pikkus	12,5 cm

Offer Sustainability

REACH-määrus	REACH-deklaratsioon
ELi RoHS direktiiv	Vastavus ELi RoHS deklaratsioon
Elavhõbedavaba	Jah
RoHS eranditeave	Jah
Hiina EoHS regulatsioon	Hiina RoHS deklaratsioon Toode ei kuulu Hiina RoHS sfääri. Ainedeklaratsioon teavitamiseks.