



### Main

Range of product	Esmi addressable components for ELC range
Product or component type	Output module

### Complementary

[Ue] rated operational voltage	15...32 V DC
Current consumption	175 µA 27 V DC standby 220 µA nominal 4 mA
Load current	5 A 250 V AC relay output 5 A 30 V DC relay output
Colour	Grey
Material	PS (polystyrene)
Provided equipment	Isolator
Cable cross section	0...2,5 Mm <sup>2</sup>
Mounting location	Indoor Outdoor
Length	176 Mm
Height	57 Mm
Width	126 Mm
Net weight	320 G

### Environment

Standards	EN 54-17 EN 54-18
Product certifications	CPR
IP degree of protection	IP55
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

### Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	6 Cm
Pakendi laius 1	12,8 Cm
Pakendi pikkus 1	18,2 Cm
Pakendi kaal 1	387 G

## Offer Sustainability

REACH-määrus	<a href="#">REACH-deklaratsioon</a>
ELi RoHS direktiiv	Vastavus <a href="#">ELi RoHS Deklaratsioon</a>
Elavhõbedavaba	Jah
RoHS eranditeave	<a href="#">Jah</a>
Hiina EoHS regulatsioon	<a href="#">Hiina RoHS Deklaratsioon</a>
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : **Commercialised**