



### Main

Range of product	Esmi addressable components for ELC range
Product or component type	Mounting base

### Complementary

Product destination	Audible alarm
Colour tint	White
Device composition	Body ABS (acrylonitrile butadiene-styrene)
[Ue] rated operational voltage	16...32 V DC
Current consumption	470 µA 27 V DC standby 9.8 mA 27 V DC alarm
Signalling type	32 tones alarm
Acoustic level	79...95 dB 1 m low volume 95...103 dBA 1 m high volume
Provided equipment	Isolator
Cable cross section	0,4...2,0 Mm <sup>2</sup>
Diameter	102 Mm
Height	33 Mm
Net weight	127 G

### Environment

Standards	EN 54-3 EN 54-17
Product certifications	CPR
IP degree of protection	IP21C
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

### Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	4,6 Cm
Pakendi laius 1	10,6 Cm
Pakendi pikkus 1	10,6 Cm
Pakendi kaal 1	152 G

## Offer Sustainability

REACH-määrus	<a href="#">REACH-deklaratsioon</a>
ELi RoHS direktiiv	Vastavus <a href="#">ELi RoHS Deklaratsioon</a>
Elavhõbedavaba	Jah
RoHS eranditeave	<a href="#">Jah</a>
Hiina EoHS regulatsioon	<a href="#">Hiina RoHS Deklaratsioon</a>
WEEE	Tootest tuleb Euroopa Liidu turgul vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : **Commercialised**