



### Main

Range of product	Esmi addressable components for ELC range
Product or component type	Smoke detector Heat detector

### Complementary

[Ue] rated operational voltage	15...32 V DC 27 V DC nominal
Current consumption	310 µA 27 V DC standby 6.5 mA alarm
Provided equipment	Isolator
Output type	Alarm output 7.5 V 7.5 mA
Cable cross section	0,4...2,0 Mm <sup>2</sup>
Diameter	103 Mm
Level	High Normal Middle Low
Height	48,3 Mm with mounting base)
Product weight	94,5 G without mounting base

### Environment

Standards	Class A1R EN 54-5 EN 54-7 EN 54-17
Product certifications	CPR
IP degree of protection	IP30
Relative humidity	0...96 % non-condensing
Ambient air temperature for operation	-10...60 °C

### Pakke osad

Pakendi tüüp 1	PCE
Ühikute arv pakendis 1	1
Package 1 Height	10,8 Cm
Pakendi laius 1	10,8 Cm
Pakendi pikkus 1	36,5 Cm
Pakendi kaal 1	104 G

## Offer Sustainability

REACH-määrus	<a href="#">REACH-deklaratsioon</a>
ELi RoHS direktiiv	Vastavus <a href="#">ELi RoHS Deklaratsioon</a>
Elavhõbedavaba	Jah
RoHS eranditeave	<a href="#">Jah</a>
Hiina EoHS regulatsioon	<a href="#">Hiina RoHS Deklaratsioon</a>
WEEE	Tootest tuleb Euroopa Liidu turgudel vabaneda vastavuses erijäätmeseadustele ning see ei tohi sattuda olmeprügi sekka.

Product Life Status : **Commercialised**